

Medium Foundation Light Commercial Rooftop Units

eAPB2107 | MARCH 22, 2021

IMPORTANT DATES

First Production:

Tonnage	Voltage	Available
10	208-230/3/60	Q2
7.5	208-230/3/60	Q3
10	460/3/30	Q3
7.5	460/3/30	Q3
8.5	208-230/3/60	Q3
12.5	208-230/3/60	Q3
8.5	460/3/30	Q3
12.5	460/3/30	Q3

RATINGS:

AHRI ratings available at
AHRIDirectory.org

For more information on the new American Standard Medium Foundation, please contact your local [American Standard](#) representative.



Carry Away the Competition- Install American Standard Medium Foundation

From small to large and **now medium tonnages**, American Standard has perfected the basic HVAC equipment standards in this reliable rooftop line. Designed for immediate, like-for-like retrofit applications, the new Medium Foundation matches the competitor footprints, making replacement a quick and easy win for contractors and business owners alike.

You asked for it, American Standard Delivered:

- New medium tonnages 7.5, 8.5, 10, & 12.5 Tons complete the line up (Electric/Electric and Gas/Electric Options)
- Plug & play footprint – Ideal for like-for-like replacement
- All medium tonnages no curb adapter needed
- Same easy, hassle-free installation & service features
- Locally availability stock – quick delivery
- Competitively priced
- Commercial financing available

Competitive Comparison

The new Medium Foundation expands American Standard's 3 - 25 Ton rooftop offering.

Capacity	AMERICAN STANDARD Foundation	Carrier Weathermaker	Lennox Raider	JCI/York Prestige
3.0	✓	✓	✓	✓
4.0	✓	✓	✓	✓
5.0	✓	✓	✓	✓
6.0		✓	✓	✓
7.5	✓	✓	✓	✓
8.5	✓	✓	✓	✓
10.0	✓	✓	✓	✓
12.5	✓	✓	✓	✓
15.0	✓	✓		
17.5	✓	✓		
20.0	✓	✓		
25.0	✓	✓		

Comparing American Standard Foundation Small/Medium/ Large

New Medium Tonnages, Same American Standard Reliability

Features	Small 3—5 Tons	Medium 7.5— 12.5 Tons	Large 15— 25 Tons
Competitive	Single Footprint	Single	Dual Footprint
Energy Efficiency	12 EER/14 SEER	11.2 IEER	Up to 12.4 EER/13.2 IEER
Voltage	208/230 VAC, 460 VAC, 575 VAC	208/230 VAC, 460 VAC	208-230 VAC, 460 VAC, 575 VAC
Accessories	Factory & Field Installed	All Field Installed	Field Installed
Airflow Configuration	Convertible	Convertible	Convertible with Horizontal Kit
Warranty	1 year parts 5 year limited compressor 10 year stainless steel heat exchanger Extended Warranty Available	1 year parts 5 year limited compressor 10 year stainless steel heat exchanger Extended Warranty Available	1 year parts 5 year limited compressor 10 year stainless steel heat exchanger Extended Warranty Available
CA Title 24	Low Leak Economizer option	Low Leak Economizer option, Multi-speed Supply Fan option	Low Leak Econ option, Multi- speed Supply Fan option
Microchannel Coils	Cond. & Evap. Coils	Cond. & Evap. Coils	Cond. & Evap. Coils
Heat Options	Low & Med Cap.	Low & Med Cap.	Low, Med, & High Cap.
Heat Stages	Multi-Stage for med. heat option	Multi-Stage for med. heat option	Multi-Stage
Carrier Replacement	Curb adapter required for some models	No curb adapter required	No curb adapter required