## **Introducing the 120 Dehumidifier**



## eAPB2124 | August 10, 2021

## **IMPORTANT DATES**

First Production: September 2021 We are excited to introduce the 120 pint whole home dehumidifier to the American Standard IAQ portfolio. We now will offer 3 different sizes to meet your installing needs.

\_\_\_\_

EDHUM70H



EDHUM098



1

			-
			- 64
			100
	Antes State		100
		*	
			100
-		-	1.00
	-		. /

First Ship: September 2021

Available Now

5 years, registered

**Pricing:** 

Warranty:

WATER REMOVAL*	70 pints/day 8.75 gallons/day	98 PINTS/DAY 12.25 GALLONS/DAY	121 PINTS/DAY 15.125 GALLONS/DAY
CURRENT DRAW	5.1 AMPS	5.9 AMPS	7.3 AMPS
EFFICIENCY	5.0 PINTS/KWH	6.1 PINTS/KWH	6.1 PINTS/KWH
ENERGY FACTOR	2.4 L/KWH	2.95 L/KWH	2.95 L/KWH
BLOWER	150 CFM @ 0.0" WG 140 CFM @ 0.2" WG 130 CFM @ 0.4" WG	320 CFM @ 0.0" WG 297 CFM @ 0.2" WG 215 CFM @ 0.4" WG	350 CFM @ 0.0" WG 285 CFM @ 0.2" WG 210 CFM @ 0.4" WG
AIR FILTER	MERV-13	MERV-13	MERV-13
DIMENSIONS	12.0" W 12.0" H 28.0" D	14.5" W 19.5" H 32.4" D	14.4" W 21.0" H 32.2" D
WEIGHT	<b>55</b> LBS.	<b>81</b> LBS.	<b>91</b> LBS.
SIZING	UP TO <b>1,800</b> FT. <sup>2</sup>	UP TO <b>2,300</b> FT. <sup>2</sup>	UP TO <b>3,000</b> FT. <sup>2</sup>

\*At 80°F and 60% RH

## FEATURES OF THE 120 DEHUMIDIFIER

- Features a horizontal configuration with optional vertical discharge
- Designed for quiet operation
- Engineered for low temperature operation providing comfort year round
- Optional digital controller for outdoor air ventilation and humidity control
- Superior MERV-13 filtration to improve indoor air quality
- Ducting options for fresh outdoor air ventilation to meet ASHRAE 62.2 ventilation requirements
- Push button reset for transformer protection