

# AMERICAN STANDARD SILVER 16 3-PHASE LOW PROFILE SIDE DISCHARGE

BUILT TO A HIGHER STANDARD  
*American Standard*  
HEATING & AIR CONDITIONING

**JANUARY 29, 2020**

## » IMPORTANT DATES:

- ▶ **FIRST ORDER DATE:** January 20, 2020
- ▶ **FIRST SHIP DATE:** February 20, 2020

The First order date for "Epoxy Coated Coil" models is February 20th.

Change the 11th thru 13th digit of the model number to "COT" to special order an epoxy coated coil.

## » MODEL NUMBERS:

See tables

## » WARRANTY:

- ▶ **COMMERCIAL USE:**  
5 Year Compressor, 1 Year Coil/Parts
- ▶ **RESIDENTIAL USE:**  
10 Year Compressor, Coil/Parts

## » RATINGS:

AHRI Ratings Available at [ahridirectory.org](http://ahridirectory.org)

## FEATURES

- ▶ Up to 17 SEER and 10 HSPF
- ▶ Single stage Climatuff™ scroll compressor
- ▶ Copper tube and aluminum fin coil
- ▶ Most efficient 3-Phase side discharge units on the market
- ▶ 73-76 dBA sound levels
- ▶ 230/460 Volt models available in 3,4,5 ton capacities

## PRODUCT MANAGER

Tim Storm

✉ [tim.storm@irco.com](mailto:tim.storm@irco.com)



American Standard Heating & Air Conditioning is pleased to announce the launch of the 3-Phase Silver 16 low profile side discharge air conditioners and heat pumps for split ducted systems.

This low profile, side discharge unit is designed to meet the needs of difficult-to-install applications or tight space requirements that make standard, vertical discharge units a less than optimal solution.

MODEL FAMILY	TYPE	POWER SUPPLY	NOM CAP COOLING	DIMENSIONS HxWxD	SOUND RATING
4A7S6036A3000A	AC	208/230/3/60	35000	36"x47"x18"	73
4A7S6048A3000A	AC	208/230/3/60	46500	36"x47"x18"	76
4A7S6060A3000A	AC	208/230/3/60	56000	42"x47"x18"	76
4A7S6036A4000A	AC	460/3/60	35000	36"x47"x18"	73
4A7S6048A4000A	AC	460/3/60	46500	36"x47"x18"	76
4A7S6060A4000A	AC	460/3/60	56000	42"x47"x18"	76
4A6S6036A3000A	HP	208/230/3/60	36000	36"x47"x18"	73
4A6S6048A3000A	HP	208/230/3/60	48000	42"x47"x18"	76
4A6S6060A3000A	HP	208/230/3/60	56000	42"x47"x18"	76
4A6S6036A4000A	HP	460/3/60	36000	36"x47"x18"	73
4A6S6048A4000A	HP	460/3/60	48000	42"x47"x18"	76
4A6S6060A4000A	HP	460/3/60	56000	42"x47"x18"	76