


Due to the unprecedented supply chain challenges the industry has been facing, along with our focus on meeting customer needs in 2021, launch of the unpainted 4MXC coil has been delayed and is now expected to be introduced by early 2022.

There will be more details to be shared on the launch of the unpainted value coil later this year.

As a reminder, below is the current 4MXC line up available today.



4MXC

Table COIL-3-C — Aluminum Single Stage Cased Coil (Upflow/Downflow/Horizontal) R-410A Refrigerant

| Model Number | Cooling Capacity Range (Tons) | Coil Type | Refrigerant Control | Outlet Dim. (in.) W/H x D | Overall Dim. (in.) H x W x D | Shipping Weight (lbs.) | Line Size OD Gas | Line Size OD Liq. |
|-----------------------------|-------------------------------|-----------|---------------------|---------------------------|------------------------------|------------------------|------------------|-------------------|
| 4MXCA003AC6HCA | 1.5 - 3.0 | A | FCCV ^① | 13 x 19 | 20 x 14.5 x 21 | 51 | 3/4 | 3/8 |
| 4MXCB004AC6HCA | 1.5 - 3.0 | A | FCCV ^① | 16 x 19 | 20 x 17.5 x 21 | 55 | 3/4 | 3/8 |
| 4MXCC005AC6HCA | 2.5 - 3.0 | A | FCCV ^① | 19 1/2 x 19 | 20 x 21 x 21 | 59 | 3/4 | 3/8 |
| 4MXCB006AC6HCA | 3.0 - 4.0 | A | FCCV ^① | 16 x 19 | 26 x 17.5 x 21 | 66 | 7/8 | 3/8 |
| 4MXCC007AC6HCA | 3.0 - 4.0 | A | FCCV ^① | 19 1/2 x 19 | 26 x 21 x 21 | 70 | 7/8 | 3/8 |
| 4MXCD008AC6HCA | 3.5 - 4.0 | A | FCCV ^① | 23 x 19 | 26 x 24.5 x 21 | 74 | 7/8 | 3/8 |
| 4MXCC009AC6HCA | 3.5 - 5.0 | A | FCCV ^① | 19 1/2 x 19 | 30 x 21 x 21 | 91 | 7/8 | 3/8 |
| 4MXCD010AC6HCA | 3.5 - 5.0 | A | FCCV ^① | 23 x 19 | 30 x 24.5 x 21 | 95 | 7/8 | 3/8 |
| 4MXCB016AC6HCA ^② | 3.0 - 4.0 | A | FCCV ^① | 16 x 19 | 30 x 17.5 x 21 | 82 | 7/8 | 3/8 |
| 4MXCC017AC6HCA ^② | 3.0 - 4.0 | A | FCCV ^① | 19 1/2 x 19 | 30 x 21 x 21 | 88 | 7/8 | 3/8 |
| 4MXCD018AC6HCA ^② | 3.5 - 4.0 | A | FCCV ^① | 23 x 19 | 30 x 24.5 x 21 | 92 | 7/8 | 3/8 |

^① All coils shipped with a Fixed Metering Device (Flow Control Check Valve - FCCV). Some rated combinations require a TXV kit, ordered separately. See the coil Installer's Guide for Orifice and TXV matches.

^② Enhanced models for use in heating.